

JOTUL FRANCE SAS 3,chemin de jubin 69574 Dardilly Cedex

EN 14785:2006		AP008S_0_12 PF1230S	
Distance from combustible material X1/X2/Y	mm	800/200/400	
Combustion products emissions (CO)	Nominal heat output	%	0,007
	Reduced heat output	%	0,040
Flue gas temperature	Nominal heat output	° C	225
Thermal performance	Nominal heat output	kW	12,04
Efficiency	Nominal heat output	%	88,54
	Reduced heat output	%	93,53
Fuel type		Pellets	

DECLARATION OF PERFORMANCE According to Regulation (EU) No. 305/2011 Nr. 004723272

1	Unique identification of product-type	AP008S_0_12																												
2	Model and/or batch no. and/or series no. (Article 11-4)	PF1230S																												
3	Intended uses of the product in accordance with the applicable harmonised technical specification	Apparatus for domestic heating, fuelled with wood pellets, without hot water production																												
4	Name or trademark of the manufacturer (Article 11-5)	JOTUL FRANCE SAS 3,chemin de jubin 69574 Dardilly Cedex																												
5	Name and address of the agent (Article 12-2)																													
6	Assessment and verification system for constancy of performance (Annex 5)	System 3 - System 4																												
7	Laboratory notified	TÜV Rheinland Energie und Umwelt GmbH_ n° 2456																												
	Test report number (based on System 3)	K19232016Z1																												
8	Performance	<table border="1"> <thead> <tr> <th>Harmonised technical specifications</th> <th>EN 14785:2006</th> </tr> <tr> <th>Essential features</th> <th>Services</th> </tr> </thead> <tbody> <tr> <td>Resistance to fire</td> <td>AI</td> </tr> <tr> <td>Distance from combustible material</td> <td>Minimum distance, in mm</td> </tr> <tr> <td></td> <td>X1=800 X2=200 Y1=400 Y2=400 Z=600</td> </tr> <tr> <td>Risk of burning fuel falling out</td> <td>Pass</td> </tr> <tr> <td>Combustion products emissions (CO)</td> <td>CO 0,007 % CO 0,040 %</td> </tr> <tr> <td>Surface temperature</td> <td>Pass</td> </tr> <tr> <td>Electrical safety</td> <td>Pass</td> </tr> <tr> <td>Accessibility and cleaning</td> <td>Pass</td> </tr> <tr> <td>Mechanical resistance (to carry a chimney/flue)</td> <td>NPD</td> </tr> <tr> <td>Thermal performance</td> <td>12,04 kW 12,04 kW 0 kW</td> </tr> <tr> <td>Efficiency</td> <td>η 88,54% η 93,53 %</td> </tr> <tr> <td>Flue gas temperature</td> <td>T 225 °C</td> </tr> </tbody> </table>	Harmonised technical specifications	EN 14785:2006	Essential features	Services	Resistance to fire	AI	Distance from combustible material	Minimum distance, in mm		X1=800 X2=200 Y1=400 Y2=400 Z=600	Risk of burning fuel falling out	Pass	Combustion products emissions (CO)	CO 0,007 % CO 0,040 %	Surface temperature	Pass	Electrical safety	Pass	Accessibility and cleaning	Pass	Mechanical resistance (to carry a chimney/flue)	NPD	Thermal performance	12,04 kW 12,04 kW 0 kW	Efficiency	η 88,54% η 93,53 %	Flue gas temperature	T 225 °C
Harmonised technical specifications	EN 14785:2006																													
Essential features	Services																													
Resistance to fire	AI																													
Distance from combustible material	Minimum distance, in mm																													
	X1=800 X2=200 Y1=400 Y2=400 Z=600																													
Risk of burning fuel falling out	Pass																													
Combustion products emissions (CO)	CO 0,007 % CO 0,040 %																													
Surface temperature	Pass																													
Electrical safety	Pass																													
Accessibility and cleaning	Pass																													
Mechanical resistance (to carry a chimney/flue)	NPD																													
Thermal performance	12,04 kW 12,04 kW 0 kW																													
Efficiency	η 88,54% η 93,53 %																													
Flue gas temperature	T 225 °C																													
9	The performance of the product referred to in points 1 and 2 is consistent with the declared performance in point 8.																													

This declaration of performance is issued under the manufacturer's sole responsibility referred to in point 4.
Signed in the name and on behalf of the manufacturer by:

DATE 27.09.2016

Signature

Tel. +33 (0)4 72 52 22 40 - Fax +33 (0)4 72 52 22 45
e-mail : contact@jotul.fr - www.jotul.fr - www.scanfrance.fr
www.ildstoves.com/fr

Jotul France
3, chemin du Jubin
69574 Dardilly cedex - France

SAS au Capital de 728 400 € - 311 472 351 RCS LYON
N° TVA CE : FR 60 311 472 351 - Code NAF 4674B
...a Jotul Group Company