

Declaration of Performance (DoP)

No. C24-CPR-130910	
Product Type:	Insert appliance
Type, batch or serial number:	Jøtul C 24
Intended use of the product:	Insert burning solid fuel without water supply
Name and Address of the manufacturer:	Jøtul AS
	Postboks 1411, 1602 Fredrikstad, Norway
	Tel.: +47 69 35 90 00
	E-mail: post@jotul.no
AVCD	
AVCP: System(s) of assessment and verification of constancy op	System 3
performance (AVCP) of the construction product as set out in	
CPR, Annex V	
Notified body:	Danish Technological Institute
NB-No:	1235
Test report no:	300-ELAB-1881-EN
Declared performance:	
Harmonized technical specification	EN 13229:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm
Distance to compustible materials	
	Floor = 330
	Front = 1050
	Combustable materials inside the surround must becovered
	by insulation as decriebed in the manual
Risk of burning fuel falling out	No
Emission of combustion products	CO [0,06 %]
	NOx [119 mg/m3]
	OGC [32 mgC/m3] PM [5 mg/m3]
Surface temperature	Pass
Electrical safety	-
Cleanability	Pass
Maximum water operating pressure	-
Flue gas temperature at nominal heat output	T [295°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Normal heat output	7 kW
Room heating output	- kW
Water heating output	-*kW
Energy efficiency	η [78%]

Declaration:

The performance of the product in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Tom J. Berglind

R&D Manager

(Name and function)

Fredrikstad, September 10th 2013

(Place and date of issue)